

Appl. No. 10/806,596
Amdt. dated June 16, 2006
Reply to Office action of March 23, 2006

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1. (Currently Amended) A variable height and multiple position batch blender assembly comprising:

- (a) a batch blender being movably mounted within a lifting assembly;
- (b) the batch blender having a cover and a receiver;
- (c) the cover closing the receiver; ~~and~~
- (d) the batch blender having a filling means and a discharge means;
- (e) the cover being pivotally removable from the batch blender and the lifting assembly;
- (f) the batch blender having the capability of placing the receiver in a low position for filling;
- (g) the low position allowing for the pivotal removal and installation of the cover; and
- (h) the batch blender having the capability of placing the receiver in a high position for discharge purposes.

Claim 2. (Previously Amended) The blender assembly of Claim 2 further comprising:

- (a) the lifting assembly supporting the batch blender;
- (b) the batch blender having an agitator means mounted in the receiver;
- (c) the agitator having at least one mixing tool secured in the interior of the receiver; and
- (d) the receiver having a discharge mechanism mounted therein.

Claim 3. (Cancelled)

Please cancel Claims 3 and 10 to 17.

Appl. No. 10/806,596

Amdt. dated June 16, 2006

Reply to Office action of March 23, 2006

Claim 4. (Currently Amended) The blender assembly of Claim 2 further comprising:

- (a) the discharge means being closeable for filling the receiver;
- (b) the cover being pivotally sealable in relation to the receiver in order to close the receiver; and
- (c) the lifting assembly supporting the receiver.

Claim 5. (Currently Amended) The blender assembly of Claim 4 further comprising:

- (a) the discharge means being positioned in a bottom portion of the receiver;
- (b) the cover pivotally closing a top portion of the receiver; and
- (c) the agitator having at least one mixing tool releasably secured thereto.

Claim 6. (Original) The blender assembly of Claim 5 further comprising:

- (a) the lifting assembly including a first side arm and a second side arm;
- (b) the first side arm supporting the receiver at a first receiver side;
- (c) the second side arm supporting the receiver at a second receiver side; and
- (d) a top cross member supporting the first side arm relative to the second side arm.

Claim 7. (Original) The blender assembly of Claim 6 further comprising:

- (a) the lifting assembly including a first lifting assembly mounted in the first side arm;
- (b) the lifting assembly including a second lifting assembly mounted in the second side arm;
- (c) the first lifting assembly being secured to the first receiver side;
- (d) the second lifting assembly being secured to the second receiver side; and
- (e) the first lifting assembly cooperating with the second lifting assembly in order to raise or lower the blender as desired.

Appl. No. 10/806,596

Amdt. dated June 16, 2006

Reply to Office action of March 23, 2006

Claim 8. (Previously Amended) The blender assembly of Claim 7 further comprising:

(a) the first lifting assembly being a first hydraulic lifting assembly;

(b) the second lifting assembly being a second hydraulic lifting assembly;

(c) the first side arm being substantially parallel to the second side arm;

(d) the first side arm and the second side arm having the blender mounted there between;

(e) the first side arm and the second side arm being secured to a floor at a base end thereof;

(f) the top cross member being oppositely disposed from the floor.

Claim 9. (Previously Amended) The blender assembly of Claim 8 further comprising:

(a) the receiver having an arcuate base;

(b) the discharge means being a closeable discharge chute;

(c) the closeable discharge chute being in the arcuate base;

(d) the closeable discharge chute having the capability of closing during a filling process or a blending process;

(e) the closeable discharge chute having the capability of opening in order to remove a product from the blender; and

(f) the closeable discharge chute being adapted to place the product in a container.

Claim 10 (Cancelled).

Claim 11 (Cancelled).

Claim 12 (Cancelled).

Claim 13 (Cancelled).

Claim 14 (Cancelled).

Claim 15 (Cancelled).

Claim 16 (Cancelled).

Appl. No. 10/806,596

Amdt. dated June 16, 2006

Reply to Office action of March 23, 2006

Claim 17 (Cancelled).

Claim 18. (Currently Amended) A variable height and multiple position batch blender assembly comprising:

(a) a batch blender being movably mounted within a hydraulic lifting assembly;

(b) the batch blender having a cover and a receiver; and

(c) the batch blender having a filling means and a discharge means;

(d) the batch blender having the capability of placing the receiver in a low position for filling purposes;

(e) the batch blender having the capability of placing the receiver in a high position for discharge purposes;

(f) the lifting assembly supporting the batch blender;

(g) the batch blender having an agitator mounted in the receiver;

(h) the agitator having at least one mixing tool secured in the interior of the receiver; the receiver; and

(i) the receiver having a discharge mechanism mounted therein;

(j) the cover closing the receiver;

(k) the cover being pivotally removable from the batch blender and the lifting assembly;

(l) the lifting assembly supporting the receiver;

(m) the discharge means being closeable for filling the receiver;

(n) the cover being pivotally sealable in relation to the receiver in order to close the receiver;

(o) the lifting assembly supporting the receiver;

(p) the discharge means being positioned in a bottom portion of the receiver;

(q) the cover closing a top portion of the receiver; and

(r) the agitator having at least one mixing tool releasably secured thereto; and

(s) the low position allowing for the removal and installation of the cover.

Claim 19 (Cancelled).

Appl. No. 10/806,596

Amdt. dated June 16, 2006

Reply to Office action of March 23, 2006

Claim 20. (Currently amended) The blender assembly of ~~claim~~
~~19~~ Claim 18 further comprising:

(a) the lifting assembly including a first side arm
and a second side arm;

(b) the first side arm supporting the receiver at a
first receiver side;

(c) the second side arm supporting the receiver at a
second receiver side;

(d) a top cross member supporting the first side arm
relative to the second side arm

(e) the lifting assembly including a first lifting
assembly mounted in the first side arm;

(f) the lifting assembly including a second lifting
assembly mounted in the second side arm;

(g) the first lifting assembly being secured to the
first receiver side;

(h) the second lifting assembly being secured to the
second receiver side; and

(h) the first lifting assembly cooperating with the
second lifting assembly in order to raise or lower the
blender as desired.

Appl. No. 10/806,596

Amdt. dated June 16, 2006

Reply to Office action of March 23, 2006

Claim 21. (New) A variable height and multiple position batch blender assembly comprising:

(a) a batch blender being movably mounted within a hydraulic lifting assembly;

(b) the batch blender having a cover and a receiver; and

(c) the batch blender having a filling means and a discharge means;

(d) the batch blender having the capability of placing the receiver in a low position for filling purposes;

(e) the batch blender having the capability of placing the receiver in a high position for discharge purposes;

(f) the lifting assembly supporting the batch blender;

(g) the batch blender having an agitator mounted in the receiver;

(h) the agitator having at least one mixing tool secured in the interior of the receiver;

(i) the receiver having a discharge mechanism mounted therein;

(j) the cover closing the receiver;

(k) the cover being pivotally openable relative to the receiver;

(l) the lifting assembly supporting the receiver;

(m) the discharge means being closeable for filling the receiver;

(n) the cover being pivotally sealable in relation to the receiver in order to close the receiver;

(o) the lifting assembly supporting the receiver;

(p) the discharge means being positioned in a bottom portion of the receiver;

(q) the cover closing a top portion of the receiver; and

(r) the agitator having at least one mixing tool releasably secured thereto; and

(s) the low position allowing for the removal and installation of the cover.

Appl. No. 10/806,596
Amdt. dated June 16, 2006
Reply to Office action of March 23, 2006

FEE STATEMENT

No additional fee is due because the number and type of newly added claims are the same as the number and type of originally presented, but now cancelled claims. Nevertheless, an appropriate authorization to charge or credit the deposit account of applicant's attorney is enclosed in the required duplicate original form -- to be used if necessary.

ACKNOWLEDGMENT OF INTERVIEW

Applicant's attorney gratefully acknowledges the telephone interview granted to him by Examiner Sorkin, on April 24, 2006. During that interview, Examiner Sorkin opined that pivotally being inserted would broaden the claims. However, as presented pivotally narrows the scope of the removable cover, in accordance with the suggestion of the Examiner's action and the pivotal indication shown in Figure 4. It is hoped that this amendment complies with the spirit and letter of that interview.

In the Examiner's response to the amendment, it was stated that no agreement had been reached. With this applicant agrees. However, it was hoped that narrowing the claims would comply with the positive feelings that appeared to come from the interview, even though no indication of allowability was given.

This is a second response with a request for continued examination. The claims are substantially labeled the same as in the prior amendment after final, because that amendment was not entered.